

PRODUCT INFORMATION SHEET

A high quality flame retardant PVC insulation tape to BS EN 60454-1, BS EN 60454-2 and BS EN 60454-3.1

It is extremely flexible and offers good adhesion.

Available in Black, Red, Yellow, Blue, Green, Violet, Orange, White, Grey, Brown and Earth (Green/Yellow).

Dimensions

Width: 19mm
Length: ITR1 20 metres, ITR2 33 metres
Tolerance: Thickness +/-0.01mm, width +/-0.5mm
Cardboard core: 32mm diameter
Packaging: Pack of 10 rolls

Properties

Total Thickness: 0.13mm
Elongation: ≥160%
Peel Adhesion: ≥1.5N/cm
Tensile Strength: ≥ 20N/cm
Flammability: ≤10 seconds
Voltage Breakdown: 6Kv
Application Temp: ≤80°C

Test Method

GB7125-1999
GB7753-1987
GB2792-1998
GB7753-1987
UL510
GBT4850-2002
GBT7752-1987

For best performance this product should be stored at under 21°C and 50% relative humidity and be used within 24 months of manufacture.
The surface this tape is to be applied to should be clean, dry and free from dust or oil.

Fully compliant to current **REACH** and **RoHS** regulations.

