

PRODUCT INFORMATION SHEET

Light Duty Concrete Screws

Non-Expansion

Description:

These concrete screws offer a light-duty anchoring system that provides a rapid and effective solution for fixing into concrete, brick, stone, concrete block, and wood. This through fixing replaces traditional fixings such as nylon frame and hammer fixings, and offers a single solution for all your anchoring needs. The screw is designed to screw directly into both frame and masonry, eliminating the need for a plug. The screw is non-expansion, making it suitable for close edge fixing.

All steel, non-flammable fixing conforming to BS 7671 standard's 18th edition, which requires wiring systems to be supported by materials which are unlikely to prematurely collapse in the event of a fire.

Product Specifications

Approval: BS 7671:2018

Corrosion Rating: (1-5) 1 - Clean, dry, low humidity environments

Driver Bit Size: TX30

Finish: Zinc & Yellow Passivated

Head Type: Flat Countersunk with Ribs

Material: Carbon Steel

Point Type: Sharp

Recess Type: T-30

Substrates: Wood, Concrete, Brick, Block, Stone

Thread Coverage: Fully Threaded

Thread Type: 3 Serrated V Threads



For further product information, please contact one of the Kernow team on 01726 624600 or sales@kernow-how.com

Stock Code	Size (mm)	Drill Hole Size (mm)	Min Hole Depth (mm)	Max Fixture Thickness (mm)	Box Qty
09620	7.5x42	6	45	5	100
09621	7.5x52	6	45	10	100
09622	7.5x62	6	45	20	100
09623	7.5x72	6	45	30	100
09624	7.5x82	6	45	40	100
09637	7.5x92	6	45	40	100
09625	7.5x102	6	45	50	100
09667	7.5x112	6	45	60	100
09626	7.5x122	6	45	70	100
09684	7.5x132	6	45	80	100
09627	7.5x152	6	45	100	100
09628	7.5x182	6	45	130	100
09629	7.5x202	6	45	150	100