

## PRODUCT INFORMATION SHEET

# Light Duty Concrete Screws

## Non-Expansion

### Description:

These concrete screws offer a light-duty anchoring system that provides a rapid and effective solution for fixing into concrete, brick, stone, concrete block, and wood. This through fixing replaces traditional fixings such as nylon frame and hammer fixings, and offers a single solution for all your anchoring needs. The screw is designed to screw directly into both frame and masonry, eliminating the need for a plug. It is a high-performance fixing with the added advantages of faster installation and an instant fix. The screw is non-expansion, making it suitable for close edge fixing. It has a deep T-30 head to reduce cam out, and a zinc & yellow passivated finish. The screw has three serrated V threads for optimum insertion.

### Product Specifications

**Approval:** BS 7671:2018

**Corrosion Rating:** (1-5) 1 - Clean, dry, low humidity environments

**Driver Bit Size:** TX30

**Finish:** Zinc & Yellow Passivated

**Head Type:** Flat Countersunk with Ribs

**Material:** Carbon Steel

**Point Type:** Sharp

**Recess Type:** T-30

**Substrates:** Wood, Concrete, Brick, Block, Stone

**Thread Coverage:** Fully Threaded

**Thread Type:** 3 Serrated V Threads



Stock Code	Size (mm)	Drill Hole Size (mm)	Min Hole Depth (mm)	Max Fixture Thickness (mm)	Box Qty
09620	7.5x40	6	45	5	100
09621	7.5x50	6	45	10	100
09622	7.5x60	6	45	20	100
09623	7.5x70	6	45	30	100
09624	7.5x80	6	45	40	100
09625	7.5x100	6	45	50	100
09626	7.5x120	6	45	70	100
09627	7.5x150	6	45	100	100
09628	7.5x180	6	45	130	100
09629	7.5x200	6	45	150	100

For further product information, please contact one of the Kernow team on 01726 624600 or [sales@kernow-how.com](mailto:sales@kernow-how.com)