

**PRODUCT INFORMATION SHEET**

# Self Tapping Screws - CSK

## Description:

- Used for stitching metal or attaching to metal. A pre-drilled hole is required.  
60° Self tapping thread.
- Countersunk head gives a discreet finish into pre-countersunk holes.
- Zinc CR3 plated.
- Pozi recess.
- Manufactured to BS 4174:1972.



Order Code	Size	Driver Bit	Head Diameter	Head Angle	Box Qty
10006	6x3/8"	PZ2	7.0	80°	200
10007	6x1/2"	PZ2	7.0	80°	200
10008	6x5/8"	PZ2	7.0	80°	200
10009	6x3/4"	PZ2	8.0	80°	200
10010	6x1"	PZ2	8.0	80°	200
10012	6x1 1/4"	PZ2	8.0	80°	200
10013	6x1 1/2"	PZ2	8.0	80°	200
10019	8x3/4"	PZ2	8.0	80°	200
10020	8x1"	PZ2	8.0	80°	200
10021	8x1 1/4"	PZ2	8.0	80°	200
10023	8x1 1/2"	PZ2	8.0	80°	200
10024	8x13/4	PZ2	8.0	80°	200
10025	8x2"	PZ2	8.0	80°	200
10031	10x1"	PZ2	9.0	80°	200
10032	10x1 1/4"	PZ2	9.0	80°	200
10033	10x1 1/2"	PZ2	9.0	80°	200
10034	10x2"	PZ2	9.0	80°	200
10036	12x1 1/2"	PZ3	11.0	80°	200

All data provided is correct at the time of print, but is subject to change by Kernow Fixings; please contact one of the Kernow team on 01726 624600 or sales@kernow-how.com to obtain the latest product information at the time of purchase.