

PRODUCT INFORMATION SHEET

Self Drilling Screws For Heavy Section Steel

Description:

Used for attaching metal to heavy gauge steel (5- 12mm) without the need to pre-drill a hole. Exterior plating gives a reliable and durable corrosion resistant coating which resists over 500 hours salt-spray.

Finish:

Exterior (Silver Organic)

Head Type:

Hex

Point type:

Self-Drilling No.5

Thread Type:

Fully Threaded Metric with V Flutes & Torque Relieving Slash

Material:

Case & Core Hardened Carbon Steel

Approval:

BS EN 10666 (DIN 7504)



Order Code	Size (mm)	Fixed Washer Size (mm)	EPDM Washer Size (mmo)	Max Drill Thickness (mm)	Effective Thread Length (mm)	Drv	Box Qty
10840	5.5 x 32	12	-	12	13	8mm	100
10841	5.5 x 32/16W	12	16	12	10	8mm	100
10842	5.5 x 38	12	-	12	19	8mm	100
10843	5.5 x 38/16W	12	16	12	16	8mm	100
10844	5.5 x 55	12	-	12	36	8mm	100
10845	5.5 x 55/16W	12	16	12	33	8mm	100
10850	5.5 x 65	12	-	12	46	8mm	100
10846	5.5 x 65/16W	12	16	12	43	8mm	100
10851	5.5 x 80	12	-	12	56 Partial Thread	8mm	100
10847	5.5 x 80/16W	12	16	12	56 Partial Thread	8mm	100
10848	5.5 x 100	12	-	12	56 Partial Thread	8mm	100
10849	5.5 x 100/16W	12	16	12	56 Partial Thread	8mm	100

For further product information, please contact one of the Kernow team on 01726 624600 or sales@kernow-how.com