

## PRODUCT INFORMATION SHEET

# Rubber Support Foot (Without Strut)

Inc 3x M10 Inserts

**Description:**

The Flexi Foot Universal has been specifically designed to allow even greater flexibility, with the installer free to bolt their own 41 x 41mm, or 41 x 21mm strut of varying lengths to these feet.

The three x M10 threaded inserts integrated within the foot recess alternatively provides an anchor point for the securing of additional M10 threaded stud positioned in a vertical plane, and often finished off with a pipe support clamp to the top.

**Material Specification:**

- Foot - SBR recycled rubber SS7188:1989+ A2 2009 and BS EN1176-7:2008 UV stabilised
- Inserts - 3 x M10 threaded inserts moulded within rubber feet during manufacture
- Finish - Galvanising BS EN ISO 1461:2009
- Robust high quality material used
- Channel is compatible with industry standard fixings and fixtures
- Suitable for internal / external environments in temperatures between -40° to +80°C BS EN IEC 6006B-2-52:2008

Order Code	Description	Length (mm)	Width (mm)	Height (mm)	Safe Working Load*	Weight
22030	Flexi Foot Universal	250	185	100	125kg	2.8kg

The maximum load is 25kg per insert - and has been tested with a 4:1 safety ratio.

For further product information, please contact one of the Kernow team on 01726 624600 or [sales@kernow-how.com](mailto:sales@kernow-how.com)