

## PRODUCT INFORMATION SHEET

# Timber Screws (Wafer Torx Head)

## Exterior Plated

Designed as an alternative to the traditional coach screw mainly used for timber to timber applications. Wafer head for improved clamping and a low profile finish. Coated with a patented multi-layer corrosion resistant plating to withstand 1,000 hours salt spray test, this screw is ideal for external applications.

Also features a single slash point to reduce torque and the risk of timber splitting at low edge distance. 25° sharp point and single lead for a fast start and improved thread acceptance.

**Material:** Carbon Steel  
**Finish:** Exterior (Green Organic)  
**CE Standard:** BS EN 14592:2008  
**Recess Type:** TX Drive  
**Head Type:** Wafer



Order Code	Size	Drive	Thread L (mm)	Box Qty
09726	6.7 x 60	TX30	40	50
09727	6.7 x 75	TX30	52	50
09638	6.7 x 95	TX30	52	50
09639	6.7 x 125	TX30	52	50
09640	6.7 x 150	TX30	52	50
09641	6.7 x 175	TX30	52	50
09642	8.0 x 200	TX40	70	50
09643	8.0 x 225	TX40	70	50
09644	8.0 x 250	TX40	70	50
09645	8.0 x 275	TX40	70	25
09646	8.0 x 300	TX40	70	25
09647	8.0 x 350	TX40	70	25
09648	8.0 x 400	TX40	70	25

For further product information, please contact one of the Kernow team on 01726 624600 or [sales@kernow-how.com](mailto:sales@kernow-how.com)