

PRODUCT INFORMATION SHEET

Coarse Thread Drywall Screws (Black)

Description:

- Drywall Screws are used for fixing plasterboard and other composite boards.
- Used mainly in the partitioning and fire-proofing industry.
- They are bugle-headed to prevent bursting the plasterboard skin and have a No.2 Phillips recess.
- Fully threaded up to 50mm, partially threaded thereafter.
- Designed to pierce and drill into 0.9mm of metal channel.
- For larger gauge channel, self-drilling drywall screws are recommended.



Technical Information:

All Drywall fastenings should be driven straight and the heads should be set slightly below the plane of the surface. Once inserted the screw should be sealed and taped to avoid any contact with wet plaster or plasterboard lime. Plated in Black Phosphate to withstand 50 hours salt spray test.

Order Code	Size (mm)	Drive	Carton Qty	Box Qty
10491	3.5 x 25	PH2	16,000	1000
10492	3.5 x 32	PH2	12,000	1000
10493	3.5 x 38	PH2	12,000	1000
10494	3.5 x 35	PH2	12,000	1000
10495	3.5 x 42	PH2	8,000	1000
10388	3.5 x 45	PH2	8,000	1000
10496	3.5 x 50	PH2	6,000	1000
10389	3.5 x 55	PH2	6,000	500
10390	3.5 x 60	PH2	6,000	500
10497	4.2 x 65	PH2	4,000	500
10498	4.2 x 75	PH2	4,000	500
10499	4.8 x 100	PH2	3,000	500

For further product information, please contact one of the Kernow team on 01726 624600 or sales@kernow-how.com